

TS2GPF830B/W/B-J/W-J

PF830

Description

TS2GPF830B is Transcend PF830 Digital Photo Frames with black color. The device is designed to access and playback photos, videos and music from a variety of sources: USB Flash drives, memory cards, or it's on-board flash memory.

System Requirements

System requirements for connecting photo frame to a computer:

- 100~240V voltage power outlet for the DC adaptor.
- Desktop or notebook computer with a working USB port.
- One of the following Operating Systems:
 - Windows® 2000
 - Windows® XP
 - Windows Vista™
 - Windows® 7
 - Mac® OS 10.0 or later
 - Linux® Kernel 2.4 or later

Features

- Bright 8" (4:3) high-resolution color TFT LCD panel
- Built-in speaker for music playback
- View photos with background music from MP3s
- Supports USB flash drives and SD/SDHC/MMC/CF/microSD/M2/MS/MS PRO/MS Duo/MS PRO Duo/MS PRO-HG Duo memory cards
- 2GB of internal memory – works even without a memory card
- Full motion video playback (Motion-JPEG only)
- AOS automatic rotation sensor with adaptive on-screen interface
- Fully compliant with High-Speed USB 2.0 and backwards compatible with USB 1.1
- Direct USB connection to your PC for easy file transfers
- Select multiple photos for convenient one-step transfer to internal memory

- Slideshow, thumbnail, still picture, and zoom-in viewing options
- Attractive frame themes and animations to accent your pictures
- Important date/event reminders
- Clock, alarm and calendar functions
- Automatic Power-ON/OFF and Sleep timers
- Custom alarm clock settings - wake up to your favorite MP3 song
- User-selectable Color Modes to enhance the look of your photos

Placement



Dimensions

Side	Millimeters	Inches
Width	212.0 ± 0.50	8.35 ± 0.02
Height	172.0 ± 0.50	6.77 ± 0.02
Depth	39.0 ± 0.50	1.54 ± 0.02

TS2GPF830B/W/B-J/W-J

PF830

Specifications

Panel	8" 4:3 TFT LCD, 800x600 pixels
Speaker	Single 0.5w speaker
USB Interface	1x standard A-Type, 1x mini B-Type
Internal Storage	2GB NAND Flash
Data Retention	Up to 10 years
Navigation	8 rear-mounted buttons and remote control
Remote Control	Infrared, NEC protocol
Dimensions	212mm x 172mm x 39mm
Power Supply	Input: 100V~ 240V 0.3A, Output: 5V DC 2.0A
Operating Temperature	0°C (32°F) ~ 40°C (104°F)
Image Formats	DSC JPEG (up to 9000 x 6750), Motion JPEG.
Video Formats	(AVI & MOV; up to 720x480 @ 30FPS)
Music Formats	MP3, WMA (Non-DRM), WAV
Supported Music Bit Rates	32Kbps–320Kbps (MP3) 32Kbps–192Kbps (WMA)
Certificates	CE, FCC, BSMI
Warranty	Panel: 1-year, (maximum 4 defective pixels) Device: 2-years

Ordering Information

Transcend P/N	Memory Size	Device Description
TS2GPF830K	2GB	PF830 Black
TS2GPF830W	2GB	PF830 White
TS2GPF830K-J	2GB	PF830 Black (Japan version)
TS2GPF830W-J	2GB	PF830 White (Japan version)