

TS2GPF830B/TS4GPF830K TS2GPF830W/TS4GPF830W

PF830

Description

TS2GPF830B/TS2GPF830W/

TS4GPF830K/TS4GPF830W is Transcend PF830 Digital Photo Frames with white color. The device is designed to access and playback photos, videos and music from a variety of sources: USB Flash drives, memory cards, or its on-board flash memory.

System Requirements

System requirements for connecting photo frame to a computer:

- 100~240V voltage power outlet for the AC adapter.
- Desktop or notebook computer with a working USB port.
- One of the following Operating Systems:
 - Windows® XP
 - Windows Vista™
 - Windows® 7
 - Mac® OS 10.0 or later
 - Linux® Kernel 2.4 or later

Features

- Bright 8" (4:3) high-resolution color TFT LCD panel
- Built-in speaker for music playback
- Seven user-selectable full screen clock styles
- Multi-Calendar, and World Clock display modes
- Countdown timer function
- View photos with background music from MP3s
- Supports USB flash drives and SD/SDHC/MMC/CF/microSD/M2/MS/MS PRO/MS Duo/MS PRO Duo/MS PRO-HG Duo memory cards
- 2GB/4GB of internal memory – works even without a memory card
- Full motion video playback (up to 1280x720)
- AOS automatic rotation sensor
- Fully compliant with High-Speed USB 2.0 and backwards compatible with USB 1.1
- Direct USB connection to your PC for easy file transfers

- Select multiple photos for convenient one-step transfer to internal memory
- Slideshow, thumbnail, still picture, and zoom-in viewing options
- Attractive frame themes and animations to accent your pictures
- Important date/event reminders
- Clock, alarm, and calendar functions
- Automatic Power-ON/OFF and Sleep timers
- Custom alarm clock settings - wake up to your favorite MP3 song
- User-selectable Color Modes to enhance the look of your photos

TS2GPF830B/TS4GPF830K TS2GPF830W/TS4GPF830W

PF830

Placement



Dimensions

| Side | Millimeters | Inches |
|--------|--------------|-------------|
| Width | 212.0 ± 0.50 | 8.35 ± 0.02 |
| Height | 172.0 ± 0.50 | 6.77 ± 0.02 |
| Depth | 39.0 ± 0.50 | 1.54 ± 0.02 |

TS2GPF830B/TS4GPF830K

TS2GPF830W/TS4GPF830W

PF830

Specifications

| | | |
|--------------------------------------------------|--------------------------------------------|-------------------------------------------------------------------------|
| Panel | 8" 4:3 TFT LCD, 800x600 pixels | |
| Speaker | Single 0.5w speaker | |
| USB Interface | 1x standard A-Type, 1x mini B-Type | |
| Internal Storage | 2GB/4GB NAND Flash | |
| Data Retention | Up to 10 years | |
| Navigation | 8 rear-mounted buttons and remote control | |
| Remote Control | Infrared | |
| Dimensions | 212mm x 172mm x 39mm | |
| Power Supply | Input: 100V~ 240V 0.3A, Output: 5V DC 2.0A | |
| Operating Temperature | 0°C (32°F) ~ 40°C (104°F) | |
| Image Formats | DSC JPEG (up to 8000 x 8000), BMP | |
| Video Formats | M-JPEG | (AVI & MOV; up to 1280x720 30fps) |
| | MPEG1 | (MPG, MPEG & AVI; up to 1280x720 30fps) |
| | MPEG-4 | (MP4, AVI & MOV; up to 1280x720 30fps) (3GP; up to 1280 x 720 30fps) |
| | H.264 | (MP4, AVI & MOV; up to 1280x720 30fps) |
| | VC1 | (WMV; up to 720x576 25fps) |
| Music Formats | MP3, WMA (Non-DRM), WAV, OGG | |
| Supported Music Bit Rates | 8Kbps–320Kbps (MP3) | |
| | 22Kbps–320Kbps (WMA) | |
| | 64Kbps–320Kbps (OGG) | |
| Maximum supported number of files/folders | 8000 | |
| Certificates | CE, FCC, BSMI | |
| Warranty | Panel: 1-year | |
| | Device: 2-years | |

TS2GPF830B/TS4GPF830K TS2GPF830W/TS4GPF830W

PF830

Ordering Information

| Transcend P/N | Memory Size | Device Description |
|---------------|-------------|--------------------|
| TS2GPF830B | 2GB | PF830 Black |
| TS2GPF830W | 2GB | PF830 White |
| TS4GPF830K | 4GB | PF830 Black |
| TS4GPF830W | 4GB | PF830 White |